

SC01-TD-W0601

Smart POS Terminal



ZKTeco introduces the **SC01-TD-W0601** series, a comprehensive point-of-sale system. This series includes three models, each with a dual display and an all-in-one design. The modular design also consists of an MSR reader (optional) and an RFID reader (optional) for convenient payment and improved retail experience. Moreover, the SC01-TD-W0601 series has a fanless system with an innovative heat pipe design that supports long operating hours.

Features

- All-in-one POS with 15.6" True-Flat PCAP Touch Screen, HD & FHD LCD Screen
- Modular Design and Optionally Embedded with MSR & RFID Reader for Convenient Payment
- Hidden Cable Management for Sleek Design
- Fanless System with Innovative Heat Pipe Design to Avoid the Spread of Grease and Heat within the POS Terminal

Applications



Retail Outlets



Restaurants



Cafes



Coffee Shops



More

Specifications

Model	SC01-TD-W0601	SC01-TD-W0603	SC01-TD-W0605
CPU	Intel® Celeron® J1900 @ 1.99GHz Optional: Intel® Celeron® J6412 @ 2.00GHz	Intel® Core® i3-4010U @ 2.40GHz	Intel® Core® i5-4120U @ 2.30GHz
Memory	4GB RAM (Standard), DDR3 & DDR4, up to 8GB 64GB SSD (Standard), up to 512GB		
Display	Configuration 1: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive Touch Screen; Second: LED (8C digital tube) Configuration 2: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive Touch Screen; Second: VFD (2*20 lines) Configuration 3: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive Touch Screen; Second: 11.6" HD, 1366*768		
Material	ABS plastic		
Colour	Black and Gray, White (Optional)		
Operating System	Supported Windows System 7, 8, 10, 11		
Dimension	345*180*354mm		
Packing Dimension	385*240*415mm		
Net Weight	Configuration 1&2: 4.7Kg Configuration 3: 5.6Kg		
Gross Weight	Configuration 1&2: 5Kg Configuration 3: 5.9Kg		
Interface (s)	1* USB 3.0 5* USB 2.0 1* COM port 1* VGA port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port	4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port	4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port
Power Supply	DC12V/5A		
Wi-Fi (Optional)	IEEE 802.11 a/b/g/n/ 2.4GHz (Single-band) IEEE 802.11 a/b/g/n/ 2.4GHz /5GHz (Dual-band)		
Bluetooth	Not Support		
Speaker	2*2W (Optional)		
Peripherals (Optional)	Built-in MSR reader Built-in RFID reader		
Operating Humidity	20% to 80% RH (Non-condensing)		
Storage Humidity	20% to 80% RH (Non-condensing)		
Operating Temperature	0°C to 40°C		
Storage Temperature	-15°C to 60°C		
Certification (s)	ISO9001, CE, FCC, RoHS		

